

SC-6000

CCD Barcode Scanners



SPECIFICATIONS CHART

Operational

Optical Systems	1500 Pixel CCD sensor
CPU	32 bits
Interfaces	USB , USB-COM,RS-232

Scan Performance

Scan Speed	200 Scans/sec.
Resolution	4 mil (0.1mm)
Print Contrast	45% or more
Scan Angle	45°
Scan Width	80mm or more (PCS90%)
Scan Distance	0-30mm (PCS90% Code 39)

Symbologies

Code 39, Full ASCII Code 39, Code 32, Code 128,
 Code 93, Code 11, Codabar/NW7, All UPC/EAN/JAN code
 (EAN-13, EAN-8, UPC-A, UPC-E, EAN-128),
 Interleave 2 of 5, STD 2 of 5, Industrial 2 of 5, matrix 2 of 5,
 Chinese Postage Code, IATA, MSI/PLESSY,
 Italian Pharmacy Code, Telepen. GS1 databar

Electrical

Input Voltage	5V DC \pm 5%
Operation Current	100-120mA
Standby Current	50-60mA

Environmental

Operating Temperature	32°C to 105°C (0°C to 50°C)
Storage Temperature	-15°C to +140°C (-26°C to 60°C)
Humidity	10% to 90% RH
Drop	1.5M

Regularity of Compliance

CE and RoHs compliant 



SBE Direct

30, rue de PENTHIEVRE - 75008 PARIS
 TEL : 01. 42. 25. 23. 23. FAX : 01. 42. 25. 44. 00
 Site Web : www.sbedirect.com
 Courriel : contact@sbedirect.com